



# Delta<sup>®</sup> 5-E

Project \_\_\_\_\_  
 Item \_\_\_\_\_  
 Quantity \_\_\_\_\_  
 CSI Section 11400 \_\_\_\_\_  
 Approval \_\_\_\_\_  
 Date \_\_\_\_\_

Delta<sup>®</sup> 5-E

## Models Delta<sup>®</sup> 5-E



### Standard Features

- Functions as both a glass-washer and a dishwasher, accommodating wares up to 11-1/2" (292 mm) high
- Push-button start
- Electromechanical controls
- Easily accessible controls
- 3-way dispensing system for detergent, rinse additive and sanitizer
- Stainless steel wash pump
- Lower rotary wash arm and fixed upper jets
- Door safety switch
- Adjustable bullet feet
- Swing-out control box for easy service and access
- Side control panel for easy access to switches
- Dial temperature gauge for constant monitoring of temperature
- Side skirt panels
- Latch-type front (lower) panel
- Delime/manual wash switch

### Options

- Water Hammer Arrestor
- Scale Prevention System (SPS)
- Replacement cartridge for SPS (2-pack)

### Accessories

- 36-Compartment Rack
  - 4-1/8" tall (105 mm)
  - 5-5/8" tall (143 mm)
  - 7" tall (178 mm)
- Combination Rack
- Peg Rack
- Flat Rack
- Half Rack

## Specifications

Uses only 1.16 gallons (4.39 liters) of water per cycle	11-1/2" (292 mm) wash chamber clearance
Cleans 40 racks per hour	Gravity drain
1,440 glasses per hour	Built-in waste accumulator
90-second operating cycle	Sustaining heating element maintains final rinse between 120°F (49°C) and 140°F (60°C)
Powerful 3/4 hp wash pump motor	Removable end plugs on lower wash arm and removable upper jets
Built-in chemical pumps	Durable 304 stainless steel construction
Air-gap water inlet	



Intertek





# Delta® 5-E

**SIDE VIEW**

**FRONT VIEW**

**OVERHEAD VIEW**

A - Incoming Water Connection  
 B - Drain Connection - 2" IPS  
 C - Electrical Connection Point

NOTE: All vertical dimensions are at lowest point due to adjustable bullet feet and may be raised an additional 2 3/4".

MODEL NO.	MACHINE DIMENSIONS					SHIPPING INFORMATION					
	INSIDE CLEARANCE HEIGHT	INSIDE CLEARANCE WIDTH	INSIDE CLEARANCE DEPTH	DOOR OPEN DEPTH	WALL CLEARANCE	WEIGHT	CLASS	CUBE	HEIGHT	WIDTH	DEPTH
Delta® 5-E	11-1/2" (292 mm)	20-1/4" (514 mm)	20-1/2" (521 mm)	36-3/4" (933 mm)	2" (51 mm)	210 lbs (95 kg)	92.5	28.2 cu. ft.	51" (1295 mm)	29" (737 mm)	33" (838 mm)

APPROXIMATE TOTAL AMP LOADS	
115/60/1	16.0

OPERATING CAPACITY	
Racks per Hour	40
Dishes per Hour	1,000
Glasses per Hour	1,440

WASH PUMP	
Wash Pump	3/4 hp

OPERATING CYCLE	
Wash Cycle (seconds)	40
Rinse Cycle (seconds)	24
Dwell Time (seconds)	18
Total Cycle (seconds)	85

BOOSTER HEATER	
Rinse Tank Booster Heater	2.0 kW

OPERATING TEMPERATURES	
Wash (minimum)	120° F (48.9° C)
Wash (recommended)	140° F (60° C)

WATER REQUIREMENTS	
Gallons per Hour	46.4 gal (176 L)
Flow Rate (GPM)	6.33 gal (24 L)
Flow Pressure (PSI)	15 - 25
Waterline Size (IPS)	1/2"
Drainline Size (OD)	2"
Tank Capacity	1.16 gal (4.39 L)
Wash Pump Capacity (GPM)	61 gal (231 L)

SANITIZERS AVAILABLE	
Sodium Hypochlorite	50 PPM
Iodophor	12 PPM

**HOW TO SPECIFY:** Delta® 5-E

**Jackson WWS, Inc.**

Shipping Address: 6209 North U.S. Highway 25E, Gray, KY 40734  
 Mailing Address: P.O. Box 1060, Barbourville, KY 40906  
 Telephone: 888-800-5672 • Fax: 606-523-1799  
 Email: info@jacksonwws.com  
 07610-004-13-56 [04/29/14]

[www.jacksonwws.com](http://www.jacksonwws.com)

*We reserve the right to change specifications in this bulletin without incurring any obligation for equipment previously or subsequently sold.*