DishStar HT-E

- **▶** Flexible Cycle Times
- ▶ Less Water
- Outstanding Results

- High temperature undercounter
- Recirculating wash design with fresh water rinse
- Low water consumption 0.65 gallons per rack
- Built-in booster heater with Sani-Sure™ technology ensures proper rinse temperature
- Three selectable timed cycles for warewashing flexibility and performance
- Digital LED control panel
- Double-wall construction
- Automatic pumped drain for both floor and wall drain installations
- Powerful 1 HP stainless steel wash pump motor
- Built-in chemical pumps and priming switches











DishStar® HT-E



DishStar HT-E provides exceptional cleaning performance and high-temperature sanitizing while consuming only 0.65 gallons of water per rack. The one minute and forty second cycle allows for 27 racks per hour which is enough capacity to clean 675 dishes or 972 glasses per hour. Simple to operate with automatic fill, push button start and three selectable cycles for Normal, Heavy and Extra Heavy soil loads. Perfect for coffee shops, bars, quick service restaurants, small healthcare facilities, day care centers and convenience stores.

ADDITIONAL FEATURES



Halo Wash Arm



Digital LED Control Panel



Interchangeable Scrap Baskets

OPERATING CYCLE TIMES (Seconds) / OPERATING CAPACITY (Racks per Hour)

| OPERATING CYCLE | CYCLE TIME | RACKS PER HOUR | GALLONS PER HOUR |
|-----------------|------------|----------------|------------------|
| Normal | :100 | 27 | 17.55 |
| Heavy | :180 | 17 | 11.05 |
| Extra Heavy | :300 | 10 | 6.50 |